

PRODUCT DATA SHEET

GREASE BLACK MP

GREASE Black MP is multi-purpose covering a wide variety of moderate service applications. It is formulated with lithium 12-hydroxy stearate soap base and solvent-refined high-viscosity index mineral base oils to act as the lubricant. It contains graphite antioxidants and can with stand oil separation. The graphite provides mild EP characteristics. It also performs under moderate to high loads.

BENEFITS

- Good lubrication under moderate to heavy shock loading
- Long service life.
- Resistance to water washing in moderate conditions.
- Good dispensing characteristics

APPLICATIONS

GREASE Black MP is recommended for the lubrication of automotive chassis fittings and bearings and for general industrial lubrication where service conditions are moderate to Heavy. It may be used in passenger cars, vans, trucks, farm tractors and general industrial equipment, machine tools and home appliances.

PRODUCT CHARACTERISTICS*

PROPERTIES	UNITS	VALUE	TEST METHOD
NLGI GRADE	-	3	-
Color	-	Brown Black	Visual
Texture	-	Smooth	Visual
Thickener Type	-	Lithium	-
Mineral Oil Viscosity @ 40 °C	mm ² /s	200.0	ASTM D-445
Mineral Oil Viscosity @ 100 °C	mm ² /s	17.5	ASTM D-445
Dropping Point (min)	°C	195	ASTM D-2265
Worked Penetration at 25 °C	mm/10	200/250	ASTM D-217
Oil Separation, mass % (max)	% mass	5.0	ASTM D-1742
Operation Temp	°C	-10 to 120	-
Graphite	% mass	0.7%	-
Product Code		0100	

*The information and figures given here are typical of current production and conform to specification, minor variations may occur.

