

PRODUCT DATA SHEET

GREASE MP (JOR)

PETROMIN GREASE MP 2 is multi-purpose covering a wide variety of moderate service applications. It is formulated with a lithium 12-hydroxy stearate soap base and solvent-refined high-viscosity index mineral base oils to act as the lubricant.

It contains special chemical additives, which enhanced oxidation resistance and special type of polymer to withstand oil separation.

BENEFITS

- Long service life.
- Resistance to water washing in moderate conditions.
- Good dispensing characteristics.

APPLICATIONS

PETROMIN GREASE MP 2 is recommended for the lubrication of automotive chassis fittings and bearings and for general industrial lubrication where service conditions are moderate.

It may be use in passenger cars, vans, trucks, farm tractors and general industrial equipment, machine tools and home appliances.

PRODUCT CHARACTERISTICS*

PROPERTIES	UNITS	VALUE	TEST METHOD
NLGI GRADE	-	2	-
Color	-	Light Brown	Visual
Texture	-	Smooth	Visual
Thickener Type	-	Lithium	-
Mineral Oil Viscosity @ 40 °C	mm ² /s	200.0	ASTM D-445
Mineral Oil Viscosity @ 100 °C	mm ² /s	17.5	ASTM D-445
Dropping Point (min)	°C	190	ASTM D-2265
Worked Penetration at 25 °C	mm/10	266/295	ASTM D-217
Oil Separation, mass % (max)	% mass	5.0	ASTM D-1742
Operation Temp	°C	-10 to 120	-
Base Number	mg KOH/g	<1.0	ASTM D-2896
Sulphated Ash	%mass	<0.5	ASTM D-874
Zinc	ppm	<20	ASTM D-4951
Product Code		0200	

*The information and figures given here are typical of current production and conform to specification, minor variations may occur.

