

SPEEDBOARD TC W3

PETROMIN SPEEDBOARD 2-S Engine Oil is blended for two-stroke water or air-cooled outboard gasoline engines. It is inhibited with ashless detergent additives and diluents to provide easier mixing with the fuel.

BENEFITS

- Controls combustion chamber and spark plug deposits build-up.
- Excellent miscibility with gasoline.
- Keeps pistons, rings, plugs and exhaust ports clean.
- Resistance to low temperature gel formation.
- Protects against rust by fresh or salt water.

SPECIFICATIONS & APPROVALS

Petromin Speedboard TC W3 has the following Builder Approvals:

- NMMA TC W3

APPLICATIONS

It is recommended for high output two-stroke water or air cooled gasoline engines. It should be added with the gasoline in the ratio as recommended by the equipment manufacturer. Not recommended for use in four-stroke engines.

PRODUCT CHARACTERISTICS*

PROPERTIES	UNITS	VALUE	TEST METHOD
Specific Gravity @ 15 °C	-	0.875	ASTM D-4052
Viscosity @ 40 °C	mm ² /s	47.0	ASTM D-445
Viscosity @ 100 °C	mm ² /s	7.70	ASTM D-445
Flash Point, COC	°C	132	ASTM D-92
Color	-	Bluish Green	ASTM D-1500
Pour Point	°C	-27	ASTM D-97
Product Code		1190	

*The information and figures given here are typical of current production and conform to specification, minor variations may occur.

