



SAFETY DATA SHEET

CHALLENGER EXCEL PREMIUM GX-500

Section 1. Identification

Material name:	CHALLENGER EXCEL PREMIUM GX-500
Product Code	144043
SDS no.	SDS 144043
<u>Relevant identified uses of the substance or mixture and uses advised against</u>	
Use of the substance/ mixture	Automotive engine crankcase lubricant. For specific application advice see appropriate Technical Data Sheet or consult our company representative
Manufacturer Supplier	Technolube L.L.C P.O.BOX: 116636, Techno Park, Dubai, United Arab Emirates www.technolubeuae.com Tel: +971 4 801 8444 Fax: +971 4 886 7014
Emergency Telephone Number	Technical Services Department Telephone: +966 12 215 7000

Section 2. Hazard(s) identification

Classification of the
substance or mixture

Not classified

GHS label elements:

Hazard Pictograms: No hazard pictogram is used

Signal word: No signal word is used

Hazard statement: Not applicable

Precautionary statement:

Prevention: Not applicable

Response: Not applicable

Storage: Not applicable

Disposal: Not applicable

Other hazards which do
not result in classification

Not applicable



SAFETY DATA SHEET

Section 3. Composition and ingredient information

Substance/ mixture Mixture

Components	CAS No.	Percent
Hydrotreated heavy paraffinic	64742-54-7	80-90%
Performance Additives	Mixture	<20%

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check and remove any contact lenses. Get medical attention
Skin contact	No specific first aid measures are required. As a precaution, remove clothing and shoes if contaminated. To remove the material from skin, use soap and water.
Inhalation	If inhaled, remove the person to fresh air. Get medical attention if symptoms
Ingestion	Do not induce vomiting. As a precaution, get medical advice.
Symptoms caused by exposure	Not available
Special Treatment	No special treatment

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media In case of fire, use Foams, dry chemicals, CO₂, nylons and powders

unsuitable extinguishing media Do not use water

Protection Equipment Heat resistant suit and gloves, Self-contained breathing apparatus

Special Risks None

Special Measures Not required

Combustion Products CO₂, H₂O, CO (in defect of air), nitrogen, sulfur and phosphorus oxides

Section 6. Accidental release measure

Precautions for the Environment Hazard of physical fouling to coasts, soils, etc. due to low solubility and high viscosity of the oils. Avoid the material entering water intakes

Clean-up Method Treat as an accidental oil spill or leak; avoid dispersion of the material with mechanical barriers. Remove with physical or chemical treatment

Personal Precautions Avoid prolonged contact with contaminated clothes or with the product

Personal Protection Gloves and goggles or face shield

Section 7. Handling and storage

Precautions for safe handling

General Precautions Avoid prolonged contact and inhalation of mists and vapors
Specific conditions Safety goggles and gloves should be used

Precautions for safe storage

Storage condition Containers properly labeled and sealed, placed in cool and
Incompatible materials Strong oxidants
Dangerous practices Not available

Section 8. Exposure control/ Personal protection

Control parameters:

Exposure Level Not available

Inhalation Low vapor pressures: The product is slightly volatile at room temperature and does not present special risks. In presence of heated oils, wear protective masks to avoid vapor inhalation

Skin Gloves
Eye Safety goggles



Other Showers and eye-washers in the working area
Specific Hygiene measure Good work practices to minimize exposure and adoption of good Personal hygiene

Exposure Level TLV (typical base oil) = 0.016 PPM at 20°C (saturated vapor Concentration);
 TLV/TWA (ACGIH) = 5mg/m³ (oil mist); TLV/STEL (ACGIH) = 10mg/m³ (oil mist)

Section 9. Physical and chemical properties

Information on basic physical and chemical properties

Appearance:

Physical state: Liquid
Color: Brownish Oil
Specific Gravity (at 15°C): 0.8596(typical)
Flash point: 220 °C
Explosive Properties: Not available
Oxidizing Properties: Not available
Water Solubility: Insoluble (100 PPM max. H₂O)
Solubility: Organic solvents
Vapor Density: Not available
Vapor Pressure: Not available
Viscosity at 100°C: 14.79 cSt (typical)
Pour Point: -36 °C (typical)
Boiling Point: Not available



SAFETY DATA SHEET

Section 10. Stability and reactivity

Reactivity	Stable under recommended transport storage conditions
Chemical stability	Stable under normal temperature pressures
Polymerization Risk	Not available
Materials to Avoid	Strong oxidants react with oils and organic materials
Hazardous Decomposition products	Not available
Condition to Avoid	Exposure to open flames

Section 11. Toxicological information

Routes of Exposure	Contact with skin, eyes and inhalation. Ingestion is not frequent.
Acute and chronic Effects	No malignant acute effects are known. Chronic effects due to repeated exposures are irritation, dermatitis and acne
Carcinogenicity	Not available
Reproductive Toxicity	No evidences
Medical Conditions which increase Hazard to Exposure	Respiratory tract deficiencies and dermatological problems

Section 12. Ecological information

Pollutant Potential:

Persistence and Degradability the material is oily and viscous and floats on water. It presents a high physical fouling potential, mainly in sea-spills; by contact, destroys small aquatic organisms and makes living difficult for upper organisms, not allowing the sunlight to reach underlying marine ecosystems, affecting its normal development.

Mobility/Bioaccumulative Potential it does not present bioaccumulative problems in living organisms or incidence in the tropic food chain, although it may cause long-term adverse effects in the aquatic environment, due to its high physical fouling potential

Eco toxicological Effect: Dangerous for aquatic life in high concentrations (spills).

Section 13. Disposal consideration

Disposal Methods (surplus) Recycling and recovery of base oils when possible

Disposal (waste) Only in specific prepared and controlled areas. Avoid releasing oils to sewers because they can destroy water treatment plant Microorganisms. Do not attempt to clean containers since residue is difficult to remove; dispose in a safe way.

Handling (waste) Labeled and sealed containers. Avoid direct contact with waste oils.



SAFETY DATA SHEET

Section 14. Transport information

Special Precautions	Stable at room temperature and during transport. Store in cool well ventilated areas.
UN Number	Not regulated
Road (ADR)/ Rail (RID) /River (ADNR)	Not regulated
Airline (IATA-ACAO)	Not regulated
Marine (IMO-IMDG)	Not regulated
Special precautions for user	Not available

Section 15. Regulatory information

Regulation	CERCLA/SARA - Section 302 Extremely Hazardous Substances and TPQs (in pounds) This material does not contain any chemicals subject to the reporting requirements of SARA 302 and 40 CFR 372.
CERCLA/SARA - Section 311/312 (Title III Hazard Categories)	Acute Health: No Chronic Health: No Fire Hazard: No Pressure Hazard: No Reactive Hazard: No
CERCLA/SARA - Section 313 and 40 CFR 372	This material does not contain any chemicals subject to the reporting requirements of SARA 313 and 40 CFR 372
EPA (CERCLA) Reportable Quantity (in pounds)	This material does not contain any chemicals with CERCLA Reportable Quantities
California Proposition 65	This material does not contain any chemicals which are known to the State of California to cause cancer, birth defects or other reproductive harm at concentrations that trigger the warning requirements of California Proposition 65
Canadian	This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the Regulations. WHMIS Hazard Class: None
National Chemical Inventories	All components are either listed on the US TSCA Inventory, or are not regulated under TSCA. All components are either on the DSL, or are exempt from DSL listing requirements
U.S. Export Control Classification Number	EAR99



SAFETY DATA SHEET

Section 16. Other information

History:

Date of Issue 10/29/2018
Revision Version Version 2.0
Status: Final
Previous Issue Date

Guide to Abbreviations

CAS Chemical Abstracts Service
ACGIH American Conference of Governmental Industrial Hygienists
CASRN Chemical Abstracts Service Registry Number
CEILING Ceiling Limit (15 minutes)
CERCLA The Comprehensive Environmental Response, Compensation, and Liability Act
EPA Environmental Protection Agency
IARC International Agency for Research on Cancer
LEL Lower Explosive Limit
NE Not Established
NFPA National Fire Protection Association
NTP National Toxicology Program
OSHA Occupational Safety and Health Administration
PEL Permissible Exposure Limit (OSHA)
SARA Superfund Amendments and Reauthorization Act
STEL Short Term Exposure Limit (15 minutes)
TLV Threshold Limit Value (ACGIH)
TWA Time Weighted Average (8 hours)
UEL Upper Explosive Limit
WHMIS Worker Hazardous Materials Information System (Canada)

Disclaimer of Expressed and implied Warranties

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of our knowledge and belief, accurate and reliable as of the date indicated. However no representation, warranty or guarantee is made as to its accuracy, reliability or completeness.

It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use.