

SUPER ULTRA 7

A new generation of automotive oils based on revolutionary concepts meeting the performance level required by today's gasoline engines. PETROMIN SUPER ULTRA 7 is blended with the most advanced additive package, which enables it to give exceptional performance under most severe operating conditions. It provides effective protection against oxidation, wear and corrosion under high temperature operations and remains a stable multigrade.

Petromin Ultra 7 provides good cold starting and high resistance to sludge, low volatility characteristics, low oil consumption and is fully compatible with the catalytic converters and exhaust emission control equipment.

BENEFITS

- Excellent engine protection.
- Eliminates seasonal oil changes.
- Maintains a high order of engine cleanliness.
- Better control of deposit formation.
- Better oxidation stability at high temperatures.
- Excellent shear stability, maintain viscosity grade.
- Protects against rust, wear and sludge formation.
- Compatible with catalytic converters.
- Suitable for mixed fleet operation.

APPLICATIONS

PETROMIN SUPER ULTRA 7 recommended for gasoline and diesel engine passenger and commercial vehicles of every make and type, turbocharged or naturally aspirated, which require API SL/CF quality oil. It can also be used for engines where API Service Category SJ and earlier categories are recommended.

It exceeds the performance requirements of most European, Japanese and American car manufacturers.

SPECIFICATIONS & APPROVALS

Petromin Super Ultra 7 has the following Builder Approvals:

- API SL

Petromin Super Ultra 7 meets or exceeds the requirements of:

- ACEA A2/B2-96



PRODUCT DATA SHEET

PRODUCT CHARACTERISTICS*

PROPERTIES	UNITS	VALUE			TEST METHOD
SAE GRADE	-	15W-40	20W-50	10W-40	-
Specific Gravity @ 15 °C	-	0.887	0.894	0.877	ASTM D-4052
Viscosity @ 40 °C	mm ² /s	109.5	165.0	101.2	ASTM D-445
Viscosity @ 100 °C	mm ² /s	14.9	19.0	15.0	ASTM D-445
Viscosity Index	-	141	130	155	ASTM D-2270
Flash Point, COC	°C	220	240	218	ASTM D-92
Base Number	mg KOH/g	7.6	7.6	7.6	ASTM D-2896
Sulphated Ash	% wt.	0.99	0.99	0.99	ASTM D-874
Pour Point	°C	-27	-24	-30	ASTM D-97
Product Code		1570	1560	1580	

*The information and figures given here are typical of current production and conform to specification, minor variations may occur.

