

PRODUCT DATA SHEET

CROWN TURBOMAX T-4

Turbomax T-4 Series heavy duty oil is developed primarily for high out naturally aspirated or supercharged diesel engines, Operating under moderate conditions. Perfomax HD4 is formulated from High mineral base oils and chemical additives which provide dispersant, detergent, anti-oxidant, anti-wear, anti-rust properties.

BENEFITS

- Excellent protection against the effect of high-Sulphur fuels.
- Improved resistance to ring sticking, ring and cylinder wear, valve and combustion deposits.
- Good Protection against rust and corrosion.

PERFORMANCE LEVEL

Meets and Exceeds:

- API CF

APPLICATION

Turbomax T-4 is recommended for use in diesel engine fitted in automotive, agriculture and construction equipment's, operating in fleet and construction business where relatively moderate Sulphur fuel is used and other severe service factors are considered.

PRODUCT CHARACTERISTIC

PROPERTIES	UNITS	VALUE	TEST METHOD
SAE GRADE	-	50	-
Specific Gravity @ 15 °C	-	0.8954	ASTM D-4052
Viscosity @ 40 °C	mm ² /s	210.9	ASTM D-445
Viscosity @ 100 °C	mm ² /s	21.50	ASTM D-445
Viscosity Index	-	112	ASTM D-2270
Flash Point, COC	°C	256	ASTM D-92
Pour Point	°C	-6	ASTM D-97
Sulphated Ash	m%	1.59	ASTM D-874
Base Number	mg KOH/g	11.2	ASTM D-2896
Color	-	Green	ASTM D-1500
Product Code	-	175044	-