

PRODUCT DATA SHEET

SUPERFLEET LD

A super high-performance, premium quality, heavy duty diesel engine oil designed for the most severe performance requirements of modern, highly rated turbocharged diesel engines in road transport & off-highway operations. It contains high alkalinity reserve to reduce acid formation.

It meets the latest performance requirements of most European and American engine builders for high output diesel engines.

BENEFITS

- Extends overhaul intervals.
- Effective control on bore polishing.
- Low and controlled oil consumption temperatures.
- Allows extended oil drain period.
- Maintains excellent engine cleanliness.
- Outstanding thermal stability.
- Excellent shear stability stays in grade throughout service life.
- Maximum control of piston deposits & ring sticking.
- Suitable for mixed fleet operations.

SPECIFICATIONS & APPROVALS

Meets or exceeds the requirements of:

- API CI-4
- MB 228.3
- VOLVO VDS-3
- ALLISON C4

APPLICATIONS

Superfleet LD is suitable for use in a variety of highly turbocharged and naturally aspirated high-speed diesel engines. It has long-drain-oil characteristic and maintains performance features throughout its service life.

PRODUCT CHARACTERISTICS*

PROPERTIES	UNITS	VALUE	TEST METHOD
SAE GRADE	-	15W-40	-
Specific Gravity @ 15 °C	-	0.889	ASTM D-4052
Viscosity @ 40 °C	mm ² /s	113.5	ASTM D-445
Viscosity @ 100 °C	mm ² /s	15.3	ASTM D-445
Viscosity Index	-	141	ASTM D-2270
Flash Point, COC	°C	232	ASTM D-92
Base Number	mg KOH/g	15.1	ASTM D-2896
Sulphated Ash	% wt.	2.03	ASTM D-874
Color	-	L 3.5	ASTM D-1500
Pour Point	°C	-27	ASTM D-97
Product Code	-	2000	-

*The information and figures given here are typical of current production and conform to specification, minor variations may occur.

