

## PRODUCT DATA SHEET

### TURBODIESEL

PETROMIN TURBODIESEL is high quality multi-grade heavy-duty diesel engine oil developed from the latest lubrication technology. They exceed meet the performance requirements of naturally aspirated, supercharged, and turbo charged high output diesel engines.

#### BENEFITS

- Can be used for all seasons.
- Maintains high engine cleanliness.
- Greater control of deposit formations.
- Prolonged oil life due to high oxidation stability at high temperatures.
- Excellent shear stability, maintains its viscosity grade.
- Protects against rust, wear and sludge formation.

#### SPECIFICATIONS & APPROVALS

Petromin TURBODIESEL meets or exceeds the requirements of:

- API / CF-4

#### APPLICATIONS

PETROMIN TURBODIESEL is suitable for use in heavy duty and high speed diesel engines and are particularly suited for heavy duty truck applications. They can also be used where API CE, CD oils are recommended.

#### PRODUCT CHARACTERISTICS\*

PROPERTIES	UNITS	VALUE	TEST METHOD
SAE GRADE	-	<b>15W-40</b>	-
Specific Gravity @ 15 °C	-	0.888	ASTM D-4052
Viscosity @ 40 °C	mm <sup>2</sup> /s	111.5	ASTM D-445
Viscosity @ 100 °C	mm <sup>2</sup> /s	15.1	ASTM D-445
Viscosity Index	-	140	ASTM D-2270
Flash Point, COC	°C	238	ASTM D-92
Base Number	mg KOH/g	10.1	ASTM D-2896
Sulphated Ash	% wt.	1.323	ASTM D-874
Color	-	L 3.5	ASTM D-1500
Pour Point	°C	-27	ASTM D-97
Product Code	-	<b>2000</b>	-

\*The information and figures given here are typical of current production and conform to specification, minor variations may occur.

