

TRANSPOWER FS 75W-90

Section 1. Identification

TRANSPOWER FS 75W-90 Material name:

2880 **Product Code**

SDS 2880-1 AU SDS no.

Relevant identified uses of the substance or mixture and uses advised against

Transmission Lubricants Use of the substance/

For specific application advice see appropriate Technical Data Sheet or consult mixture

our company representative

Manufacturer **Petromin Corporation**

Supplier P.O.BOX: 1432, Jeddah 21431

Prince Sultan Road, Ayah Mall

www.petromin.com Tel: +966 12 60 8300 Fax: +966 12 608 2545

Australian International Lubricant Distributors Pty

Supplier Ltd Unit 11, 100 Hay Street, Subiaco, 6008, WA ABN 79 139 276 887

admin@ilddirect.com

Tel: 1300 558 939 Fax: +61 8 9381 1788

Technical Services Department Emergency Telephone

Number Telephone: +966 12 215 7000

Section 2. Hazard(s) identification

Classification of the Not classified as Hazardous according to criteria of National Occupational Health

substance or mixture & Safety Commission (NOHSC), Australia. Not classified as Dangerous Goods

according to the Australian Code for the Transport of Dangerous Goods by Road

and Rail.

GHS label elements:

Hazard Pictograms: No hazard pictogram is used

No signal word is used Signal word:

Hazard statement: No known significant effects or critical hazards

Precautionary statement:

Not applicable **Prevention:** Not applicable Response: Storage: Not applicable Not applicable **Disposal:**

Other hazards which do

Not applicable not result in classification

Product Name: Transpower FS 75W-90 Version#: 1.0 Product code#: 2880

Page 1 of 7 Date of issue: 09/11/2018



Section 3. Composition and ingredient information

Substance/ mixture Mixture

Components	CAS No.	Percent
Base oil: distillates hydrotreated light paraffinic	64742-55-8	20-25%
Distillates (petroleum), hydrotreated light paraffinic	64742-54-7	28-35%
Performance Additives	Mixture	30-45%

Section 4. First aid measures

Description of necessary first aid measures

In case of contact, immediately flush eyes with plenty of water for at least 15 **Eye contact**

minutes. Eyelids should be held away from the eyeball to ensure through

rinsing. Check and remove any contact lenses. Get medical attention

No specific first aid measures are required. As a precaution, remove clothing Skin contact

and shoes if contaminated. To remove the material from skin, use soap and

water.

If inhaled, remove the person to fresh air. Get medical attention if symptoms **Inhalation**

Do not induce vomiting. As a precaution, get medical advice. Inegstion

Symptoms caused by

Not available exposure

Special Treatment No special treatment

Section 5. Fire-fighting measures

Suitable extinguishing In case of fire, use Foams, dry chemicals, CO₂, nylons and powders

media

unsuitable extinguishing Do not use water

media

Heat resistant suit and gloves, Self-contained breathing apparatus **Protection Equipment**

Special Risks None

Not required **Special Measures**

CO2, H2O, CO (in defect of air), nitrogen, sulfur and phosphorus oxides **Combustion Products**

Section 6. Accidental release measure

Hazard of physical fouling to coasts, soils, etc. due to low solubility and high **Precautions for the**

Environment viscosity of the oils. Avoid the material entering water intakes

Clean-up Method Treat as an accidental oil spill or leak; avoid dispersion of the material with

mechanical barriers. Remove with physical or chemical treatment

Personal Precautions Avoid prolonged contact with contaminated clothes or with the product

Gloves and goggles or face shield **Personal Protection**

Product Name: Transpower FS 75W-90 Version#: 1.0 Page 2 of 7 Product code#: 2880 Date of issue: 09/11/2018



Section 7. Handling and storage

Precautions for safe handling & storage

Take precautions against static electricity discharges. Use proper grounding procedures. For information on the design of the storeroom, reference should be made to Australian Standard AS1940 - The storage and handling of flammable and combustible liquids. Reference should also be made to all applicable local and national regulations. Classified as a Class C2 (COMBUSTIBLE LIQUID) for the purpose of storage and handling, in accordance with the requirements of AS1940. This product should be stored and used in a well-ventilated area away from naked flames, sparks and other sources of ignition.

Dangerous practices

Not available

Section 8. Exposure control/ Personal protection

Exposure Standard

No exposure standards have been established for this material, however, the TWA National Occupational Health And Safety Commission (NOHSC) exposure standards for oil mist is 5 mg/m³.TWA (Time Weighted Average): The average airborne concentration of a particular substance when calculated over a normal eight-hour working day, for a five-day week.

Respiratory Protection



If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable vapour/mist filter should be used. Reference should be made to Australian/New Zealand Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.

Eve Protection



Safety glasses with side shields, goggles or full-face shield as appropriate recommended. Final choice of appropriate eye/face protection will vary according to individual circumstances i.e. methods of handling or engineering controls and according to risk assessments undertaken. Eye protection should conform with Australian/New Zealand Standard AS/NZS 1337 - Eye Protectors for Industrial Applications.

Hand Protection



Wear gloves of impervious material. Final choice of appropriate gloves will vary according to individual circumstances i.e. methods of handling or according to risk assessments undertaken. Reference should be made to AS/NZS2161.1: Occupational protective gloves - Selection, use and maintenance.

Body Protection

Suitable protective workwear, e.g. cotton overalls buttoned at neck and wrist is recommended. Chemical resistant apron is recommended where large quantities are handled. Industrial clothing should conform to the specifications detailed in AS/NZS 2919: Industrial clothing.

Product Name: Transpower FS 75W-90

Product code#: 2880

Page 3 of 7

Date of issue: 09/11/2018



Section 9. Physical and chemical properties

Information on basic physical and chemical properties

Appearance:

Liquid **Physical state:**

Color: Light Amber 0.857 (typical) Specific Gravity (at 15°C):

Flash point: 210 ºC

Explosive Properties: Not available **Oxidizing Properties:** Not available

Insoluble (100 PPM max. H₂O) Water Solubility:

Organic solvents **Solubility:** Not available Vapor Density: Not available **Vapor Pressure:** Viscosity at 40°C: 96.79 cSt (typical) **Pour Point:** -42 °C (typical) Not available **Boiling Point:**

Section 10. Stability and reactivity

Reactivity Stable under recommended transport storage conditions

The product is stable **Chemical stability**

Not available **Polymerization Risk**

Materials to Avoid Strong oxidants react with oils and organic materials

Hazardous Decomposition Not available

products

Condition to Avoid Exposure to open flames

Section 11. Toxicological information

Contact with skin, eyes and inhalation. Ingestion is not frequent. **Routes of Exposure**

No malignant acute effects are known. Chronic effects due to repeated **Acute and chronic Effects**

exposures are irritation, dermatitis and acne

Not available Carcinogenicity

No evidences **Reproductive Toxicity**

Medical Conditions which

increase Hazard to

Exposure

Respiratory tract deficiencies and dermatological problems

Product Name: Transpower FS 75W-90 Version#: 1.0

Page 4 of 7 Product code#: 2880 Date of issue: 09/11/2018



Section 12. Ecological information

Pollutant Potential:

Persistence and Degradability

the material is oily and viscous and floats on water. It presents a high physical fouling potential, mainly in sea-spills; by contact, destroys small acuatic organisms and makes living difficult for upper organisms, not allowing the

Potential

Mobility/Bioaccumulative it does not present bioaccumulative problems in living organisms or incidence in the tropic food chain, although it may cause long-term adverse effects in the acuatic environment, due to its high physical fouling potential

Eco toxicological Effect: Dangerous for acuatic life in high concentrations (spills).

Section 13. Disposal consideration

Disposal Methods (surplus)

Recycling and recovery of base oils when possible

Disposal (waste)

Only in specific prepared and controlled areas. Avoid releasing oils to sewers because they can destroy water treatment plant Microorganisms. Do not attempt to clean containers since residue is difficult to remove; dispose in a safe way.

Handling (waste)

Labeled and sealed containers. Avoid direct contact with waste oils.

Section 14. Transport information

Special Precautions Stable at room temperature and during transport. Store in cool well ventilated

areas.

Transport Information Not classified as Dangerous Goods according to the Australian Code for the

Transport of Dangerous Goods by Road and Rail.

UN Number Not regulated

Road (ADR)/ Rail (RID)

/River (ADNR)

Not regulated

Airline (IATA-ACAO) Not regulated Marine (IMO-IMDG) Not regulated

Special precautions for

user

Not available

Product Name: Transpower FS 75W-90 Version#: 1.0

Page 5 of 7 Product code#: 2880 Date of issue: 09/11/2018



Section 15. Regulatory information

Not classified as Hazardous according to criteria of National Occupational Health **Regulatory Information**

> & Safety Commission (NOHSC), Australia. Not classified as a Scheduled Poison according to the Standard for the Uniform Scheduling of Drugs and Poisons

(SUSDP).

Poisons Schedule Not Scheduled

Regulation CERCLA/SARA - Section 302 Extremely Hazardous Substances and TPQs (in

pounds):

This material does not contain any chemicals subject to the reporting requirements of

SARA 302 and 40 CFR 372.

CERCLA/SARA - Section 311/312 (Title III Hazard

Categories)

Acute Health: No **Chronic Health:** No

Fire Hazard: No Pressure Hazard: No Reactive Hazard: No

CERCLA/SARA - Section 313 This material does not contain any chemicals subject to the reporting

requirements of SARA 313 and 40 CFR 372

EPA (CERCLA) Reportable

Quantity (in pounds)

and 40 CFR 372

This material does not contain any chemicals with CERCLA Reportable

Quantities

California Proposition 65 This material does not contain any chemicals which are known to the State of

California to cause cancer, birth defects or other reproductive harm at

concentrations that trigger the warning requirements of California Proposition

65

Canadian This product has been classified in accordance with the hazard criteria of the

> Controlled Products Regulations (CPR) and the MSDS contains all the information required by the Regulations. WHMIS Hazard Class: None

National Chemical

Inventories

All components are either listed on the US TSCA Inventory, or are not regulated

under TSCA. All components are either on the DSL, or are exempt from DSL

listing requirements

U.S. Export Control Classification Number EAR99

Product Name: Transpower FS 75W-90 Version#: 1.0 Page 6 of 7 Product code#: 2880 Date of issue: 09/11/2018



Section 16. Other information

History:

Date of Issue18/12/2018Revision VersionVersion 1.0

Status: Final

Previous Issue Date

Guide to Abbreviations CAS Chemical Abstracts Service

ACGIH American Conference of Governmental Industrial Hygienists

CASRN Chemical Abstracts Service Registry Number

CEILING Ceiling Limit (15 minutes)

CERCLA The Comprehensive Environmental Response, Compensation, and

Liability Act

EPA Environmental Protection Agency

IARC International Agency for Research on Cancer

LEL Lower Explosive Limit

NE Not Established

NFPA National Fire Protection Association

NTP National Toxicology Program

OSHA Occupational Safety and Health Administration

PEL Permissible Exposure Limit (OSHA)

SARA Superfund Amendments and Reauthorization Act

STEL Short Term Exposure Limit (15 minutes)

TLV Threshold Limit Value (ACGIH)
TWA Time Weighted Average (8 hours)

UEL Upper Explosive Limit

WHMIS Worker Hazardous Materials Information System (Canada)

Disclaimer of Expressed and implied Warranties

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of our knowledge and belief, accurate and reliable as of the date indicated. However no representation, warranty or guarantee is made as to its accuracy, reliability or completeness.

It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use.

Product Name: Transpower FS 75W-90

Product code#: 2880

Page 7 of 7

Date of issue: 09/11/2018