

## PRODUCT DATA SHEET

### GEARBOX OIL

PETROMIN GEARBOX OIL Series are high-quality gear lubricants blended from solvent-refined mineral base oils and selected chemical additives. Due to their high shear stability, they provide excellent protection for gears and can be used over a wide range of temperatures. They also provide protection against foaming of oil, and wear and rusting of gears.

#### BENEFITS

- Formulated for automotive high-speed gears.
- Excellent lubrication without channeling at low temperatures.
- Superior protection against rusting, pitting and corrosion.
- Suitable for heavy-duty service in truck and bus gears operating at high temperatures.
- Provide good protection against corrosion.

#### SPECIFICATION & APPROVALS

Petromin Gearbox Oil meets or exceeds the requirements of:

- API GL-4

#### APPLICATIONS

Recommended for the type of service characteristics of gears, particularly hypoid, in passenger cars and other automotive-type equipment operated under high-speed/low torque and low speed/high torque conditions.

#### PRODUCT CHARACTERISTICS\*

PROPERTIES	UNITS	VALUE		TEST METHOD
SAE Grade	-	<b>90</b>	<b>140</b>	-
Specific Gravity @ 15 °C	-	0.894	0.906	ASTM D-4052
Viscosity @ 40 °C @ 100 °C	mm <sup>2</sup> /s	198.0	434.2	ASTM D-445
	mm <sup>2</sup> /s	17.8	30.3	ASTM D-445
Viscosity Index	-	96	99	ASTM D-2270
Flash Point, COC	°C	232	236	ASTM D-92
Pour Point	°C	-9	-9	ASTM D-97
Color	-	3.0	L 3.5	ASTM D-1500
Product Code	-	<b>3010</b>	<b>3020</b>	

\*The information and figures given here are typical of current production and conform to specification, minor variations may occur.

