

## PRODUCT DATA SHEET

### FLUSHING OIL

PETROMIN FLUSHING OIL is a light-bodied mineral oil for flushing automotive, industrial and agricultural engines, gearboxes, transmission and hydraulic systems. It is compatible with other petroleum oils used in circulating systems.

#### BENEFITS

- Circulates freely, reaching even remote locations.
- Scavenges dirt and deposits from surfaces.
- Non-corrosive.
- Protects surfaces from rusting.

#### APPLICATIONS

PETROMIN FLUSHING OIL is used for flushing engines, manual gearboxes and axles, circulating and hydraulic systems and other applications where low-viscosity oil is required.

#### PRODUCT CHARACTERISTICS\*

PROPERTIES	UNITS	VALUE	TEST METHOD
Specific Gravity @ 15 °C	-	0.9011	ASTM D-4052
Viscosity @ 40 °C	mm <sup>2</sup> /s	24	ASTM D-445
@ 100 °C	mm <sup>2</sup> /s	320.9	ASTM D-445
Viscosity Index	-	95	ASTM D-2270
Flash Point, COC	°C	210	ASTM D-92
Pour Point	°C	-12	ASTM D-97
Color	-	0.5	ASTM D-1500
Product Code		<b>3110</b>	

\*The information and figures given here are typical of current production and conform to specification, minor variations may occur.

