

## PRODUCT DATA SHEET

### ATF II D

PETROMIN AUTOMATIC TRANSMISSION FLUID (ATF) II-D is formulated from special high-quality solvent refined mineral base oils combined with VI Improvers, anti-oxidants, anti-wear agents, detergents, anti-foaming agents and special additives to provide controlled friction or lubricity characteristics.

ATF II-D serves as a power-transmission fluid in the torque converter, hydraulic fluid in the control and servo systems, as a lubricant for bearing and gears and as a friction-controlling medium for bands and clutches.

#### BENEFITS

- Effective frictional characteristics for smooth shifting.
- Excellent fluidity at low temperature applications.
- Good protection against wear.
- Reduced foaming and fluid loss under severe service conditions.
- Protection against high-temperature deposits in heavy-duty service.

#### PERFORMANCE LEVEL

Petromin ATF II D meets or exceeds the requirements of:

- DEXRON II D

#### APPLICATIONS

PETROMIN ATF II D is formulated to meet the requirements for passenger car and light truck automatic transmissions, power steering and other hydraulic systems.

#### PRODUCT CHARACTERISTICS\*

PROPERTIES	UNITS	VALUE	TEST METHOD
Specific Gravity @ 15 °C	-	0.850	ASTM D-4052
Viscosity @ 40 °C	mm <sup>2</sup> /s	33.19	ASTM D-445
Viscosity @ 100 °C	mm <sup>2</sup> /s	7.18	ASTM D-445
Viscosity Index	-	187	ASTM D-2270
Flash Point, COC	°C	192	ASTM D-92
Pour Point	°C	-42	ASTM D-97
Color	-	Red	ASTM D-1500
<b>Product Code</b>		<b>3300</b>	

\*The information and figures given here are typical of current production and conform to specification, minor variations may occur.

