

## ATF DEXRON IIIH

*Automatic Transmission Fluid Dexron IIIH is high performance, multifunctional fluid designed to meet the requirements of General Motors Dexron III, Ford Mercon & Allison C-3 or C-4 specifications. It provides good oxidation stability & friction resistance ensuring consistent & smooth power shifting.*

### BENEFITS

- Friction modifier provides smooth shifting & trouble free operation.
- Excellent oxidation resistance resulting in cleaner transmissions.
- Compatible with all types of rubbers, elastomers and metals, and providing protection against wear and leakage.
- Excellent low-temperature fluidity.
- Better shear stability.
- Completely miscible at any proportions with other allied automatic transmission fluids with no separation or color change.

### PERFORMANCE LEVEL

Meets:  
 DEXRON..... IIIH  
 FORD MERCON... M950309  
 ALLISON..... C-3 & C-4

### APPLICATIONS

*ATF DEXRON IIIH is formulated to meet the automatic transmission fluid requirements of modern vehicles. Also meets the hydraulic fluid requirements of certain industrial and mobile equipment.*

### PRODUCT CHARACTERISTICS

PROPERTIES	UNITS	VALUE	TEST METHOD
Specific Gravity @ 15 °C	-	00.8496	ASTM D-4052
Viscosity @ 40 °C	mm <sup>2</sup> /s	36.0	ASTM D-445
Viscosity @ 100 °C	mm <sup>2</sup> /s	7.392	ASTM D-445
Viscosity Index		177	ASTM D-2270
Flash Point, COC	°C	208	ASTM D-92
Pour Point	°C	-48	ASTM D-97
Color	-	RED	Visual
Copper Strip, 3Hrs @ 100°C	°C	1B	ASTM D-130
Viscosity Brookfield	-		
@ -20°C (max.)	cP	1500	GM 6137-M
@ -40°C (max.)	cP	2000s0	GM 6137-M
Product Code	-	331042	-