

PRODUCT DATA SHEET

ATF DEXRON II E

PETROMIN AUTOMATIC TRANSMISSION FLUID (ATF) DEXRON II-E is formulated from special high-quality solvent refined mineral base oils combined with VI improvers, anti-oxidants, anti-wear agents, detergents, anti-foaming agents and special additives to provide controlled friction or lubricity characteristics.

ATF II-E serves as a power-transmission fluid in the torque converter, hydraulic fluid in the control and servo systems, as a lubricant for bearing and gears and as a friction-controlling for bands and clutches.

BENEFITS

- Effective frictional characteristics for smooth shifting.
- Excellent fluidity at low temperature applications.
- Good protection against wear.
- Reduced foaming and fluid loss under severe service condition.
- Protection against high-temperature deposits in heavy-duty service.

PERFORMANCE LEVEL

Petromin ATF DEXRON II E meets or exceeds the requirements of:

- DEXRON II E

APPLICATIONS

Rec PETROMIN ATF DEXRON II E is formulated to meet the requirements for passenger car and light truck automatic transmissions, power steering and other hydraulic systems. Recommended for application where former DEXRON II D oils are in use.

PRODUCT CHARACTERISTICS*

PROPERTIES	UNITS	VALUE	TEST METHOD
Specific Gravity @ 15 °C	-	0.850	ASTM D-4052
Viscosity @ 40 °C	mm ² /s	32.0	ASTM D-445
Viscosity @ 100 °C	mm ² /s	7.0	ASTM D-445
Viscosity Index	-	187	ASTM D-2270
Flash Point, COC	°C	188	ASTM D-92
Pour Point	°C	-45	ASTM D-97
Color	-	RED	ASTM D-1500
Product Code		3340	

*The information and figures given here are typical of current production and conform to specification, minor variations may occur.

