

SPEEDX SP2

Speedx SP2 is a monograde engine oils developed for gasoline engine oil .They provide excellent control over engine wear and deposit build up and protection against rust and corrosion .

BENEFITS

- Keep Engine Cleaner
- Good protection against corrosion and wear
- Good Oxidation Stability

PERFORMANCE LEVEL

MEETS:

- API SF

APPLICATIONS

Speedx SP2 Series is used in gasoline engines where oils conforming to API Service Category API SF is required.

PRODUCT CHARACTERISTICS

| PROPERTIES | UNITS | VALUE | TEST METHOD |
|--------------------------|--------------------|---------------|-------------|
| SAE GRADE | - | 50 | - |
| Specific Gravity @ 15 °C | - | 0.8981 | ASTM D-4052 |
| Viscosity @ 40 °C | mm ² /s | 221.8 | ASTM D-445 |
| Viscosity @ 100 °C | mm ² /s | 20.51 | ASTM D-445 |
| Viscosity Index | - | 108 | ASTM D-2270 |
| Flash Point, COC | °C | 254 | ASTM D-92 |
| Sulphated Ash | m% | 1.12 | ASTM D-874 |
| Base Number | mg KOH/g | 7.53 | ASTM D-2896 |
| Pour Point | °C | -9 | ASTM D-97 |
| Color | - | 6.0 | - |
| Product Code | - | 365042 | - |