

SUPER DIESEL PLUS

Petromin Super Diesel plus is high quality multigrade diesel engine oil developed for modern diesel engines, formulated from thermally stable mineral base oils, offering excellent dispersant/detergent characteristics, anti-oxidant and anti-wear properties with relatively high alkalinity reserve.

BENEFITS

- Diesel engine oil for American, European and Japanese vehicles. Suitable for direct and indirect fuel injection.
- Effective control over high temperature piston deposits and soot accumulation.
- Excellent protection against corrosive wear caused by high-sulfur fuels.
- Extended engine life.
- Improved resistance to ring sticking, ring and cylinder liner wear, valve and combustion deposits.
- Improved fuel economy.
- Reduced oil consumption.

SPECIFICATIONS & APPROVALS

Petromin Super Diesel Plus meets or exceeds the requirements of:

- API / CH-4

APPLICATIONS

Petromin Super Diesel plus is recommended for use in modern highly rated diesel engines installed in construction, transport, agriculture and other heavy-duty equipment. Its long drain capability meets the requirement almost to all leading diesel engine manufacturer. It is recommended for both on-highway and off-highway engines for low emissions middle age & and old engines of conventional design fueled by low and high sulfur diesel fuels.



PRODUCT DATA SHEET**PRODUCT CHARACTERISTICS***

PROPERTIES	UNITS	VALUE	TEST METHOD
SAE GRADE	-	15W-40	-
Specific Gravity @ 15 °C	-	0.889	ASTM D-4052
Viscosity @ 40 °C	mm ² /s	107.5	ASTM D-445
Viscosity @ 100 °C	mm ² /s	14.84	ASTM D-445
Viscosity Index	-	142	ASTM D-2270
Flash Point, COC	°C	237	ASTM D-92
Base Number	mg KOH/g	10.0	ASTM D-2896
Sulphated Ash	% wt.	1.5	ASTM D-874
Color	-	2.5	ASTM D-1500
Pour Point	°C	-27	ASTM D-97
Product Code	-	3840	-

*The information and figures given here are typical of current production and conform to specification, minor variations may occur.

