

PRODUCT DATA SHEET

CROWN SUPER COOLANT

SUPER COOLANT/ANTIFREEZE™ is an innovative blend of organic acids and inorganic inhibitors formulated to provide extended life protection to all liquid cooled internal combustion engines. This coolant is based on Hybrid Organic Acid Technology (HOAT) and provides superior protection against corrosion. Super Coolant/Antifreeze™ is significantly more durable than conventional coolants and is compatible with other similar HOAT branded coolants. Super Coolant/ Antifreeze™ is an ethylene glycol-based formulation suitable for passenger cars, light trucks, and heavy duty vehicles in all industries including Transport, Marine, Earthmoving and Mining.

Super Coolant/ Antifreeze™ meets and/or exceeds the following standards:

ASTM D 3306 Specification: "Standard Specification for Glycol Base Engine Coolant for Automobile and Light-Duty Service" and the International standard ASTM D 4985 "Standard Specification for Low Silicate Ethylene Glycol Base Engine Coolant for Heavy Duty Engines.

BENEFITS

- Super Coolant/ Antifreeze™ is based on HOAT technology which offers superior engine protection for up to 3 years or 150,000 miles
- Super Coolant/ Antifreeze™ prevents wet liner cavitation's erosion, and provides exceptional protection to aluminum surfaces
- Super Coolant/ Antifreeze™ is a silicate free formulation that prevents problems such as water pump weepage, solder bloom, and silica gel buildup in vehicle engines - yet still offers aluminum protection
- Super Coolant/ Antifreeze™ offers corrosion protection in cooling systems containing metals such as copper, solder, brass, steel, cast iron, and aluminum
- Super Coolant/Antifreeze™ reduces maintenance costs since it is fully formulated - no additional SCA's required at initial fill or top-off

APPLICATION

- Formulated to meet ASTM standards.
- Silicate and Phosphate Free.
- Based on innovative HOAT formula.
- Super Coolant/Antifreeze™ is formulated to meet or exceed the performance requirements of the following antifreeze specification and/or recommended practices:

PRODUCT DATA SHEET

GM 6277M
 Komatsu KES 07.892
 Cummins Bulletin 3666132
 John Deere H-5

Ford WSS-M97851-A1
 Chrysler MS9769
 Mercedes Benz Sheet 325.3

PRODUCT CHARACTERISTIC

Super Coolant formulated with the finest quality of water as advised by the standard specification ASTM D 3306-08a mentioned below:

PROPERTIES	VALUE			
	Green	Green	Green	Green
Appearance	Green	Green	Green	Green
Density (20°C)	1.054	1.067	1.0541	1.1098
Antifreeze Glycols mass %	40%	50%	30%	94%
Corrosion Inhibitors mass %	<5%	<5%	<5%	< 5%
pH	7.5-8.5	7.5-8.5	8.7	7.5-8.5(50% Dilution)
Phosphates ppm	0	0	0	0
Product Code	437044	120244	543044	597044