

PRODUCT DATA SHEET

CROWN TURBOMAX PREMIUM TX-8

Turbomax Premium TX-8 is premium quality automotive engine oil meeting the latest European and American standards. The superior additive chemistry used in manufacturing Perfomax Turbomax Premium TX-8 is proven to provide the highest diesel engine performance level.

BENEFITS

- Universal engine oil for old and new diesel engine fuelled by both high and low sulphur diesel.
- Proven field-tested engine oil with extended drain period capability.
- Excellent TBN retention for moderate sulphur diesel fuel operation.
- Effective control over high temperature piston deposits and soot accumulation.

PERFORMANCE LEVEL

Meets and Exceeds:

- API CI-4
- MB 228.3
- MAN M3275-1
- VOLVO VDS-3
- ACEA E7
- CAT ECF-1a
- MACK E O-N
- JASO DHD-1 (Level)
- RENAULT VI RLD -2
- MTU/ DDC TYPE2
- CUMMINS CES 2007 8 /77 /76
- ALLISON C-4

APPLICATION

Turbomax Premium TX-7 is suitable for use in modern heavy duty diesel vehicles for both on and off-highway applications. It is suitable for use in CUMMINS, MTU, VOLVO, MAN, MERCEDES-BENZ, MACK and RENAULT manufacturers.

PRODUCT CHARACTERISTIC

PROPERTIES	UNITS	VALUE	TEST METHOD
SAE GRADE	-	15W-40	-
Specific Gravity @ 15 °C	-	0.8702	ASTM D-4052
Viscosity @ 40 °C	mm ² /s	116.2	ASTM D-445
Viscosity @ 100 °C	mm ² /s	15.58	ASTM D-445
Viscosity Index	-	141	ASTM D-2270
Flash Point, COC	°C	226	ASTM D-92
Pour Point	°C	-30	ASTM D-97
Base Number	mg KOH/gm	10.7	ASTM D-2896
Sulphated Ash	% wt.	1.5	ASTM D-874
CCS Viscosity@ -20 °C	cP	5650	ASTM D-5293
Color	-	L 3.5	ASTM D-1500
Product Code	-	458044	-