

PRODUCT DATA SHEET

CROWN FORMULA FX-7

Formula FX7 is a high performance lubricant using fully synthetic technology, specially developed for Gasoline and Diesel car engines, meeting and complying with the requirements of the latest direct injection engines and conventional engines as well.

BENEFITS

- Outstanding resistance to oxidation, corrosion, wear, and high temperature deposits.
- Ensuring sustainable high performance, thus meeting the needs of the engines in terms of extended and better oil drain intervals
- Guaranteeing high 5 constant quality by excellent detergent properties giving greater engine cleanliness for enhanced performance.
- High Viscosity Index resulting in stable viscosity during operation.
- Fully miscible with other engine oils.
- Superior anti - wear properties protecting the engine's most sensitive parts.
- Easy cold start and ideal lubrication at elevated temperature, ensures low oil consumption and cold start protection against wear.

APPLICATION

- Suitable for usage in all modern Gasoline Engine that uses direct fuel injections.
- All turbocharged and multi-valved engines.
- Suitable for most severe operating conditions, on highways, dense city traffic 5 in extreme weather conditions.
- Suitable & exceeds the performance requirements of most European, Japanese and American car manufacturers.

PERFORMANCE LEVEL

Meets and Exceeds:

- API SP

PRODUCT CHARACTERISTIC

PROPERTIES	UNITS	VALUE	TEST METHOD
SAE GRADE	-	15W-40	-
Specific Gravity @ 15 °C	-	0.8705	ASTM D-4052
Viscosity @ 40 °C	mm ² /s	113.7	ASTM D-445
Viscosity @ 100 °C	mm ² /s	15.4	ASTM D-445
Viscosity Index	-	143	ASTM D-2270
Flash Point, COC	°C	228	ASTM D-92
Base Number	mg KOH/gm	8.0	ASTM D-2896
Pour Point	°C	-33	ASTM D-97
Product Code		494044	-