

PRODUCT DATA SHEET

CROWN TURBOMAX ULTRA TX-8

Turbomax Ultra TX-8 is Ultra High Performance Diesel (UHPD) engine oil designed to meet the most severe performance requirements of the latest high output, low emission European diesel engines. It is formulated with fully synthetic base oils and superior additive to provide the highest diesel engine performance levels.

BENEFITS

- Universal engine oil for old and new diesel engine fuelled by both high and low sulphur diesel.
- Proven field-tested engine oil with extended drain period capability.
- Excellent TBN retention for moderate sulphur diesel fuel operation.
- Effective control over high temperature piston deposits and soot accumulation.

PERFORMANCE LEVEL

Meets and Exceeds:

- API CI-4
- MB 228.5
- MAN M3277
- Renault RLD-2
- MTU Type 3
- Scania LDF-2
- MACK E O-N
- Volvo VDS-3
- Cummins 20078/77

ACEA E7/E4

APPLICATION

Turbomax Ultra TX-8 is suitable for use in modern heavy duty diesel vehicles for both on and off-highway applications. It is suitable for use in CUMMINS, MTU, VOLVO, MAN, MERCEDES-BENZ, MACK and RENAULT manufacturers.

PRODUCT CHARACTERISTIC

PROPERTIES	UNITS	VALUE	TEST METHOD
SAE GRADE	-	10W-40	-
Specific Gravity @ 15 °C	-	0.8601	ASTM D-4052
Viscosity @ 40 °C	mm ² /s	96.47	ASTM D-445
Viscosity @ 100 °C	mm ² /s	14.88	ASTM D-445
Viscosity Index	-	162	ASTM D-2270
Flash Point, COC	°C	240	ASTM D-92
Pour Point	°C	-33	ASTM D-97
Base Number	mg KOH/gm	12.5	ASTM D-2896
Sulphated Ash	% wt.	1.6	ASTM D-874
Color	-	3.5	ASTM D-1500
Product Code	-	553044	-