

## PRODUCT DATA SHEET

### DUSTING OIL AL-500

Petromin Dusting Oil Series is high quality solvent refined paraffin oils containing no additives. Dusting Oils possess inherent oxidation stability, adequate rust prevention and lower volatility along with thermal stability.

#### BENEFITS

- Inherent oxidation stability.
- Low volatility.
- Thermally stable.
- High boiling Point

#### APPLICATIONS

Petromin Dusting Oil is suitable for bearing and gear lubrication systems where the operating conditions are not severe. Recommended for use in re-circulating and other closed oil systems. Suitable for rubber processing industry. Also useful as De-Dusting oil for supply to the calciner in Aluminum manufacturing.

#### PRODUCT CHARACTERISTICS\*

PROPERTIES	UNITS	VALUE
ISO Grade	-	100
Specific Gravity @ 15 °C	-	0.8905
Viscosity @ 40 °C	mm <sup>2</sup> /s	100.30
@ 100 °C	mm <sup>2</sup> /s	11.3
Viscosity Index	-	98
Boiling Point	°C	288
Flash Point, COC	°C	248
Pour Point	°C	-6
Color	-	2.0
Product Code	-	5720

\*The information and figures given here are typical of current production and conform to specification, minor variations may occur.

