

#### LONG LIFE COOLANT 50%

Section 1. Identification

Material name: LONG LIFE COOLANT 50%

5901 **Product Code** SDS 5901-1 SDS no.

Relevant identified uses of the substance or mixture and uses advised against

Engine coolant Use of the substance/

For specific application advice see appropriate Technical Data Sheet or consult mixture

our company representative

Manufacturer **Petromin Corporation** 

Supplier P.O.BOX: 1432, Jeddah 21431

Prince Sultan Road, Ayah Mall

www.petromin.com Tel: +966 12 60 8300 Fax: +966 12 608 2545

**Emergency Telephone Technical Services Department** Number Telephone: +966 12 215 7000

# Section 2. Hazard(s) identification

Harmful if swallowed Classification of the

substance or mixture

**GHS label elements: Hazard Pictograms:** 

Warning Signal word:

Harmful if swallowed. **Hazard statement:** 

**Precautionary statement:** 

**Prevention:** Wash with plenty of water and soap thoroughly after handling.

Call a POISON CENTER or doctor/physician. Response:

IF SWALLOWED: rinse mouth.

Storage: Store locked up.

Dispose of contents/container to hazardous or special waste **Disposal:** 

collection point.

No specific dangers known, if the regulations/notes for storage and

Other hazards which do handling are considered. not result in classification

**Product Name: Long Life Coolant 50%** Version#: 2.0 Date of issue: 28/02/2019

Page 1 of 6 Product code#: 5901



# Section 3. Composition and ingredient information

Substance/ mixture Mixture

| Components           | CAS No.    | Percent  |
|----------------------|------------|----------|
| Monoethyleneglycol   | 107-21-1   | 96-97.7% |
| 2-ethylhexanoic acid | 19766-89-3 | 2-3%     |
| borax pentahydrate   | 12179-04-3 | 0.3-1%   |

#### Section 4. First aid measures

Description of necessary first aid measures

Eye contact May cause irritation to eyes. Rinse immediately with plenty of water for 15

minutes holding the eyelids open. Seek medical attention if irritation or

symptoms persist.

Skin contact May cause irritation to skin. May cause dermatitis. Wash off immediately with

plenty of soap and water. Remove contaminated clothing. Seek medical

attention if irritation or symptoms persist.

Inhalation Harmful by inhalation. Inhalation may cause nausea and vomiting. May cause

dizziness and headache. Move the exposed person to fresh air. Seek medical

attention.

Ingestion

Harmful if swallowed. Ingestion may cause nausea and vomiting. Ingestion is

irritating to the respiratory tract and may cause damage to the central nervous

system. DO NOT INDUCE VOMITING. If swallowed, seek medical advice

immediately and show this container or label.

# Section 5. Fire-fighting measures

**Extinguishing media** 

Suitable extinguishing

media

Use as appropriate: Carbon dioxide (CO2), Dry chemical, Foam.

Special Risks None

Special Measures Self-contained breathing apparatus. Wear protective clothing

#### Section 6. Accidental release measure

Precautions for the

Environment

Do not allow product to enter drains. Prevent further spillage if safe.

Clean-up Method

Absorb with inert, absorbent material. Transfer to suitable, labelled containers

for disposal. Clean spillage area thoroughly with plenty of water.

Personal Precautions Ensure adequate ventilation of the working area. Wear suitable protective

equipment.

Personal Protection Gloves and goggles or face shield

Product Name: Long Life Coolant 50%

Product code#: 5901

Page 2 of 6

Date of issue: 28/02/2019



#### Section 7. Handling and storage

Avoid contact with eyes and skin. Ensure adequate ventilation of the working **Precautions for safe** 

handling area. Adopt best Manual Handling considerations when handling, carrying and

**Specific conditions** Safety goggles and gloves should be used

**Precautions for safe** 

storage

Other

None

**Storage condition** 

Keep in a cool, dry, well ventilated area. Keep containers tightly closed.

Not available **Dangerous practices** 

# Section 8. Exposure control/ Personal protection

**Control parameters:** 

Not available **Exposure Level** 

Inhalation No specific recommendation made, but respiratory protection must be used if

the general level exceeds the Occupational Exposure Level (OEL). Wear full face

mask supplied with: Gas cartridge (organic substances).

Gloves Skin

Safety goggles Eye

Showers and eye-washers in the working area

Good work practices to minimize exposure and adoption of good Personal hygien **Specific Hygiene measure** 

**Exposure Level** TLV (typical base oil) = 0.016 PPM at 20°C (saturated vapor Concentration);

TLV/TWA (ACGIH) = 5mg/m3 (oil mist); TLV/STEL (ACGIH) = 10mg/m3 (oil mist)

# Section 9. Physical and chemical properties

Information on basic physical and chemical properties

**Appearance:** 

Liquid Physical state: Color: Green

Specific Gravity (at 15°C): 1.112 g/cm3 **Equilibrium Boiling Point** 165 ºC

**Explosive Properties:** Not available Not available **Oxidizing Properties:** 

-18 ºC **Freezing Point:** 7.0 - 8.6pH value Soluble **Solubility in Water** 

**Product Name: Long Life Coolant 50%** Version#: 2.0 Page 3 of 6 Product code#: 5901 Date of issue: 28/02/2019



# Section 10. Stability and reactivity

Reactivity Stable under recommended transport storage conditions

Stable under normal temperature pressures **Chemical stability** 

Not available **Polymerization Risk** 

Strong oxidants react with oils and organic materials **Materials to Avoid** 

Hazardous Decomposition Not available

products

**Condition to Avoid** Exposure to open flames

#### Section 11. Toxicological information

**Routes of Exposure** Contact with skin, eyes and inhalation. Ingestion is not frequent.

No malignant acute effects are known. Chronic effects due to repeated Acute and chronic Effects

exposures are irritation, dermatitis and acne

Carcinogenicity Not available No evidences Reproductive Toxicity

Medical Conditions which

increase Hazard to **Exposure** 

Respiratory tract deficiencies and dermatological problems

#### Section 12. Ecological information

**Pollutant Potential:** 

Persistence and Elimination information:

Degradability > 70 % DOC reduction (28 d) (OECD 301 A (new version)) Readily

Potential

Mobility/Bioaccumulative Bioaccumulation potential:

Accumulation in organisms is not to be expected.

Volatility: The substance will not evaporate into the atmosphere from the water

surface.

Adsorption in soil: Adsorption to solid soil phase is not expected.

**Eco toxicological Effect:** Dangerous for aquatic life in high concentrations (spills).

#### Section 13. Disposal consideration

**Disposal Methods (surplus)** 

Must be disposed of or incinerated in accordance with local regulations

Disposal (waste) Only in specific prepared and controlled areas. Avoid releasing oils to sewers

> because they can destroy water treatment plant Microorganisms. Do not attempt to clean containers since residue is difficult to remove; dispose in a safe

way.

Handling (waste) Labeled and sealed containers. Avoid direct contact with waste oils.

**Product Name: Long Life Coolant 50%** Version#: 2.0 Page 4 of 6 Product code#: 5901 Date of issue: 28/02/2019



# Section 14. Transport information

**Special Precautions** Stable at room temperature and during transport. Store in cool well ventilated

areas.

Not regulated **UN Number** 

Road (ADR)/ Rail (RID)

/River (ADNR)

Not regulated

Airline (IATA-ACAO) Not regulated

Marine (IMO-IMDG) Not regulated

Special precautions for

user

Not available

#### Section 15. Regulatory information

Regulation CERCLA/SARA - Section 302 Extremely Hazardous Substances and TPQs (in

pounds):

This material does not contain any chemicals subject to the reporting requirements of

SARA 302 and 40 CFR 372.

**CERCLA/SARA - Section** 

311/312 (Title III Hazard

Categories)

**Acute Health:** No **Chronic Health:** No

Fire Hazard: No

**Pressure Hazard:** No Reactive Hazard: No

CERCLA/SARA - Section 313 This material does not contain any chemicals subject to the reporting

and 40 CFR 372

requirements of SARA 313 and 40 CFR 372

**EPA (CERCLA) Reportable** 

Quantity (in pounds)

This material does not contain any chemicals with CERCLA Reportable

Quantities

**California Proposition 65** This material does not contain any chemicals which are known to the State of

California to cause cancer, birth defects or other reproductive harm at

concentrations that trigger the warning requirements of California Proposition

65

Canadian This product has been classified in accordance with the hazard criteria of the

> Controlled Products Regulations (CPR) and the MSDS contains all the information required by the Regulations. WHMIS Hazard Class: None

**National Chemical** 

**Inventories** 

All components are either listed on the US TSCA Inventory, or are not regulated under TSCA. All components are either on the DSL, or are exempt from DSL

listing requirements

**U.S. Export Control Classification Number**  EAR99

**Product Name: Long Life Coolant 50%** 

Version#: 2.0 Page 5 of 6 Product code#: 5901 Date of issue: 28/02/2019



# Section 16. Other information

#### **History:**

Date of Issue28/02/2019Revision VersionVersion 2.0

Status: Final

**Previous Issue Date** 

Guide to Abbreviations CAS Chemical Abstracts Service

**ACGIH** American Conference of Governmental Industrial Hygienists

**CASRN** Chemical Abstracts Service Registry Number

**CEILING** Ceiling Limit (15 minutes)

**CERCLA** The Comprehensive Environmental Response, Compensation, and

**Liability Act** 

**EPA** Environmental Protection Agency

IARC International Agency for Research on Cancer

**LEL** Lower Explosive Limit

NE Not Established

**NFPA** National Fire Protection Association

NTP National Toxicology Program

**OSHA** Occupational Safety and Health Administration

PEL Permissible Exposure Limit (OSHA)

**SARA** Superfund Amendments and Reauthorization Act

STEL Short Term Exposure Limit (15 minutes)

TLV Threshold Limit Value (ACGIH)
TWA Time Weighted Average (8 hours)

**UEL** Upper Explosive Limit

WHMIS Worker Hazardous Materials Information System (Canada)

Disclaimer of Expressed and implied Warranties

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of our knowledge and belief, accurate and reliable as of the date indicated. However no representation, warranty or guarantee is made as to its accuracy, reliability or completeness.

It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use.

Product Name: Long Life Coolant 50%

Product code#: 5901

Page 6 of 6

Date of issue: 28/02/2019