

## PRODUCT DATA SHEET

## **SUPER EXTENDED LIFE COOLANT 50**

**SUPER EXTENDED LIFE COOLANT** is a ready to use product based on OAT (Organic Acid Technology) formulated to provide long life protection to all liquid cooled internal combustion engines. Super Extended Life Coolant is significantly more durable than conventional coolants & it contains no phosphates, borates, nitrates, or silicates. Super Extended Life Coolant is an ethylene glycol-based formulation (50% concentration) suitable for passenger cars, light trucks, and heavyduty commercial vehicles in all industries including Transport, Marine, Earthmoving and Mining.

Super Extended Life Coolant <sup>™</sup> meets and/or exceeds the following standards:

ASTM D 3306 ,ASTM D 4985 ,AS 2108-2004,BS 6580:2010,CUNA NC 956-16,AFNOR NFR 15-601,ONORM V 5123, JIS K K 2234:2006,SAE J 1034,SANS 1251:2005 and China GB 29743-2013

### **PRODUCT HIGHLIGHTS**

- Super Extended Life Coolant 50 is based on OAT technology which offers superior engine protection for up 5 years or 600,000 km
- Super Extended Life Coolant 50 prevents wet liner cavitations erosion, and provides exceptional protection to aluminum surfaces
- Super Extended Life Coolant 50 is free of silicate, nitrites, amines, phosphates and borates, which protects engines against corrosion and deposits in the cooling system with its vital parts, coolant channels in the block and cylinder head, the radiator and water pump.
- Super Extended Life Coolant <sup>™</sup> offers corrosion protection in cooling systems containing metals such as copper, solder, brass, steel, cast iron, and aluminum
- Super Extended Life Coolant <sup>™</sup> reduces maintenance costs since it is fully formulated no additional SCA's required at initial fill or top-up





# PRODUCT DATA SHEET

## **KEY FEATURES**

- Formulated to meet various international standards.
- Ready to use
- Based on innovative OAT formula.
- Long Life Coolant 50 is formulated to meet or exceed the performance requirements of the following antifreeze specification and/or recommended practices:

Audi/Seat/Skoda/VW
Bentley / Lamborghini
DAF
TL 774-D/F
TL 774-F
MAT- 74002

Daimaler/Mercedez Benz MB Approval 325.3

DeutzFerrariDQC CB 14MY 2010

MAN
MAN 324 Type SNF
Mini Cooper D
MY2007 to MY 2011

> MTU MTL 5048

Porsche MY 1996 to MY2009

## **TYPICAL CHARACTERISTICS\***

TIFICAL CHARACTERISTICS	
	TYPICAL VALUES
Colour	Red
Density (20°C)	1 - 1.13
Glycols mass %	50.8
Freezing Point	- 42 C
рН	8.2-8.6
Code	<u>5901</u>

<sup>\*</sup>The information and figures given here are typical of current production and conform to specification, minor variations may occur.

