

## PRODUCT DATA SHEET

### DIESEL HDJ 10W

PETROMIN DIESEL HDJ 10W OIL is high quality oil suitable for diesel engines, gasoline engines, or supercharged. They provided good control over high temperature deposits, sludge, rust, corrosion and wear. PETROMIN DIESEL HDJ 10W oils are formulated with chemically stable, high VI base stocks and chemical additives that impart dispersant and detergent properties and resistance to oxidation, corrosion, wear and rusting.

#### BENEFITS

- Improved control over high-temperature varnish deposits.
- Minimize low temperature sludge build-up.
- Good protection against rust and corrosion.

#### SPECIFICATIONS & APPROVALS

##### Performance Level (Approved)

API.....SJ

#### APPLICATIONS

PETROMIN DIESEL HDJ 10W oil is recommended for use in diesel engines either naturally aspirated or supercharged. They provide good performance under conditions of high speed, high load, high-temperature operation which require API Service Category SJ.

#### PRODUCT CHARACTERISTICS\*

PROPERTIES	UNITS	VALUE	TEST METHOD
SAE GRADE	-	10W	-
Specific Gravity @ 15 °C	-	0.	ASTM D-4052
Viscosity @ 40 °C	mm <sup>2</sup> /s	9	ASTM D-445
Viscosity @ 100 °C	mm <sup>2</sup> /s	1	ASTM D-445
Viscosity Index	-	1	ASTM D-2270
Flash Point, COC	°C	2	ASTM D-92
Base Number	mg KOH/g	1	ASTM D-2896
Sulphated Ash	% wt.	0.	ASTM D-874
Color	-	-	ASTM D-1500
Pour Point	°C	-	ASTM D-97
Product Code	-	XXXX	-

\*The information and figures given here are typical of current production and conform to specification, minor variations may occur.

